



The Ingersoll Rand 236 Impactool offers professional technicians performance, comfort and durability with great value for money.

- 610 Nm (450 ft-lb) of maximum torque in reverse.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- Steel hammercase provides superior durability under the toughest use.
- Feather-touch trigger allows precise delivery of power and speed.
- 2-position power regulator and forward/reverse control.
- Silenced through-handle exhaust reduces the noise level.

Specifications at 6,2 bar (90 psi)

Part Number	236
Ordering number	80171879
Drive size (square)	1/2 in
Other available versions:	
- kit with 10 short sockets	236-SK

PERFORMANCE

Working torque in forward	25 - 200 ft-lb / 34 - 271 Nm
Maximum torque in forward	450 ft-lb / 610 Nm
Working torque in reverse	25 - 200 ft-lb / 34 - 271 Nm
Maximum torque in reverse	450 ft-lb / 610 Nm
Recommended fastener size	9/16 in / M14
Free speed	7 400 rpm
Impacts per minute	1 200

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	4,3 CFM / 122 L/min
Air consumption at load	24,0 CFM / 680 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	90,3 / 101,3 dB(A)
Vibration level / measurement uncertainty (ISO28927)	12,0 / 1,0 m/s ²

WEIGHT & DIMENSIONS

Tool weight	5,30 lb / 2,40 kg
Tool length	7,09 in / 180 mm
Shipping weight	6,00 lb / 2,70 kg
Shipping dimensions (L x W x H)	240 x 215 x 83 mm
UPC / EAN code	6 63023 02097 6
Origin	Made in China



www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.


SK4M3L

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)


SK4M14

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)


Impact sockets

For the complete range, see our accessory catalogue.


236-BOOT

45528148

Protective tool boot


IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)


Quick Release Couplings

For the complete range, see our accessory catalogue.


105-LBK1

04616090

Lubricant kit for Impacttools™ with metal housing


105-4T-6

04618930

Grease for Impacttools hammer mechanism (6 tubes)


236-TK1

80211618

Motor service kit


SK4M5L

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)


SK4M18

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)


4UA9

03070216

1/2" right-angle head
(speed reduction: 25%
torque output reduction: up to 50%)

77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7,2 mm bore (EURO 7,2 - 7,4)


Filters, regulators, lubricators

For the complete range, see our accessory catalogue.


10Z4

03875671

Oil, Class 1, no. 10, 0,12 L


Lubricants

For the complete range, see our accessory catalogue.