



**Powered by legend. The 2235QXPA 1/2" Impactool™. Super powerful, ultra durable and with that extra bit of comfort: Succeeding the legendary Thunder Gun racing tool, our brand new 2235QXPA is the racehorse you can bet on when the going gets tough. Designed after its successful predecessor, the new impact wrench rings the superior ergonomical advances of the race track right to your garage. And when push comes to shove, the 2235QXPA is just what you need. It has been put to every test conceivable, has been beaten up, dropped, tossed and pushed to the limits – just so you can be certain: The 2235QXPA gets REAL WORK done right, every time.**

- 1 220 Nm (900 ft-lb) of maximum torque in reverse - that's the best-in-class performance.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Unique reverse-bias 7-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Patented technology reduces the noise level without sacrificing the power.

## Specifications at 6.2 bar (90 psi)

Part Number	2235QXPA
Ordering number	47532836001
Drive size (square)	1/2 in
Torque settings (forward / reverse)	4 / 1
Other available versions:	

### PERFORMANCE

Maximum torque in forward	870 ft-lb / 1 180 Nm
Maximum torque in reverse	900 ft-lb / 1 220 Nm
Nut busting torque in reverse	1 300 ft-lb / 1760 Nm
Recommended fastener size	9/16 in / M14
Free speed	8 500 rpm
Impacts per minute	1 220

### AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	6.0 CFM / 170 L/min
Air consumption at load	24.0 CFM / 680 L/min
Impacting sound pressure / power (ISO15744)	91.9 / 102.9 dB(A)
Free speed sound pressure / power (ISO15744)	88.7 / 99.7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	9.0 / 2.8 m/s²

### WEIGHT & DIMENSIONS

Tool weight	4.7 lb / 2.1 kg
Tool dimensions (L x W x H)	193 x 74 x 183 mm
Shipping weight	5.5 lb / 2.5 kg
Shipping dimensions (L x W x H)	216 x 244 x 82 mm
UPC / EAN code	6 63023 12296 0
Origin	Assembled in the USA




**SK4M3L**

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)


**SK4M14**

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)


**Impact sockets**

For the complete range, see our accessory catalogue.


**2235-BOOT**

47536461001

Protective tool boot


**Filters, regulators, lubricators**

For the complete range, see our accessory catalogue.


**115-LBK1**

04616108

Lubricant kit for Impacttools™ with composite housing


**115-4T**

04616157

Grease for Impacttools with composite housing


**2235-THK1**

47517319001

Impact mechanism service kit


**SK4M5L**

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)


**SK4M18**

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)


**BMDS-4**

92842087

Cable balancer, 2-4 kg, 2 m (6-1/2 ft)


**10Z4**

03875671

Oil, Class 1, no. 10, 0.12 L


**Lubricants**

For the complete range, see our accessory catalogue.


**2235-TK1**

47517401001

Motor service kit

0