



Ingersoll Rand Pro-Series grinders, sanders and polishers are specially designed for heavy-duty production applications. With their superior power output, they are best suited for big tasks involving heavy material removal in foundries, welding shops, fabrication facilities, steel mills or shipyards.

- Powerful motor delivers 1.75 kW (2.35 HP).
- 4 500 rpm free speed.
- Internal governor maximizes speed under load, increasing your rate of material removal.
- Integral trigger safety lock prevents accidental tool start.
- Built-in mist lubricator automatically oils motor when throttle is activated.

Specifications at 6.2 bar (90 psi)

Part Number	99HL45H108-EU
Ordering number	01339563
Wheel capacity	8 in / 200 mm
Maximum wheel thickness	1 in / 25 mm
Spindle size	5/8"-11
Other available versions:	
- 150 mm (6") wheel capacity	99HL60H106-EU

PERFORMANCE

Rated power	2.35 HP / 1.75 kW
Free speed	4 500 rpm

AIR SYSTEM

Air Inlet (NPT)	1/2 in
Minimum hose size	5/8 in / 16 mm
Air consumption at load	70 CFM / 33.0 L/s

NOISE & VIBRATION

Sound pressure / power (ANSI S5.1-1971)	82.0 / 95.0 dB(A)
Vibration level / measurement uncertainty (ISO28927)	< 2.5 m/s ²

WEIGHT & DIMENSIONS

Tool weight	14.88 lb / 6.76 kg
Tool length	20.25 in / 514 mm
Shipping weight	16.0 lb / 7.3 kg
Shipping dimensions (L x W x H)	265 x 580 x 190 mm
UPC / EAN code	6 63024 00362 6
Origin	Made in the USA



Ingersoll Rand **99HL45H108-EU** **ACCESSORIES**



33304

91488205

Hose whip, 1/2" NPT, 13 mm inside diameter, 30 cm (1 ft)



Quick Release Couplings

For the complete range, see our accessory catalogue.



CO-2225

56753163

Hose clamps, 22-25 mm outside diameter, 100 pcs



50P

03875705

Oil, Class 1, no. 50, 0.5 L



IB11NMC4

25014036

IBN/IBS Series nipple, 1/2" male thread, 11 mm bore (ISO6150B / MIL-C4109)



RH-19

92536077

PVC hose, 19 mm inside diameter, 30 m



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



99V 99H-TK3

03802923

Motor service kit

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2008 Ingersoll-Rand Company — Form No. PDS_99HL45H108-EU_EN_2/2_24/01/2012

 **Ingersoll Rand**
 Industrial Technologies