

**41
Series**

Medium & Heavy Assembly Tools
Outils d'assemblage moyens et lourds
Mittlere und schwere Montagewerkzeuge
Intermedio y constantemente montaje herramientas
Medie e forte montaggio utensili

**Standard
Equipment**

**Clutch
spring(s)**

**Skinsulate™
soft touch,
non-slip grip**

**Vertical
Hanger**

**Ressort(s)
de limiteur**

**Revêtement
anti-dérapant
Skinsulate™**

**Suspension
verticale**

**Kupplungs-
federn**

**Skinsulate™
Weicher,
rutschfester
Griff**

**Vertikal-
Aufhänger**

**Muelles de
embrague**

**Empuñadura
suave,
antideslizante
Skinsulate™**

**Suspensión
vertical**

**Molle della
frizione**

**Impugnatura
morbida,
antiscivolo
Skinsulate™**

**Disp. sospen-
sione verticale**


Specifications at 90 psi – Caractéristiques à 620 kPa
 Technische Daten bezogen auf 620 kPa
 Especificaciones a 620 kPa – Caratteristiche a 620 kPa

Straight Screwdrivers
Visseuses Droites
Druckluftdreherschrauber, gerade Ausführung
Atornilladores con Empuñadura Recta
Cacciaviti con Impugnatura Diritta













41SA10PSQ4-EU

Skinsulate™
Comfort Coating



Adjustable shut-off clutch models — Modèles avec limiteur de couple réglable à coupure d'air — Modelle mit einstellbarer Abschaltkupplung — Modelos con parada automática — Modelli con frizione regolabile con blocco aria

Ref.	 Nm ⁽¹⁾	 Nm ⁽¹⁾	 Nm ⁽¹⁾	 1 min. rpm	 kg	 mm	 mm	 in	 l/min
CC LEVER + PUSH START — LEVIER + POUSÉE — HEBELSTART + SCHUBSTART — PALANCA + EMPUJE — LEVA + SPINTA									
41SA10LPQ4-EU	1.7 - 4.5	2.8 - 6.8	4.0 - 9.0	1000	1.20	277	20	1/4	790
41SA8LPQ4-EU	1.7 - 4.5	2.8 - 6.8	4.0 - 11.3	800	1.20	277	20	1/4	790
CC PUSH START — DEM. PAR POUSÉE — SCHUBSTART — ARRANQUE POR EMPUJE — AVVIAMENTO A SPINTA									
41SA17PSQ4-EU	1.7 - 4.5	2.8 - 6.8	—	1700	1.20	277	20	1/4	790
41SA10PSQ4-EU	1.7 - 4.5	2.8 - 6.8	4.0 - 9.0	1000	1.20	277	20	1/4	790
41SA8PSQ4-EU	1.7 - 4.5	2.8 - 6.8	4.0 - 11.3	800	1.20	277	20	1/4	790












Adjustable cushion clutch models
 Modèles avec limiteur de couple réglable à billes
 Modelle mit einstellbarer Rutschkupplung
 Modelos con embrague ajustable deslizante
 Modelli con frizione regolabile a cuscino



41SC10LTQ4-EU

Skinsulate™
Comfort Coating

Ref.	 Nm ⁽¹⁾	 Nm ⁽¹⁾	 Nm ⁽¹⁾	 1 min. rpm	 kg	 mm	 mm	 in	 l/min
CC LEVER START — DÉM. PAR LEVIER — HEBELSTART — ARRANQUE POR PALANCA — AVVIAMENTO A LEVA									
41SC17LTQ4-EU	1.1 - 4.5	1.7 - 6.8	—	1700	1.40	277	20	1/4	565
41SC10LTQ4-EU	1.1 - 4.5	1.7 - 9.0	—	1000	1.40	277	20	1/4	565
CC PUSH START — DEM. PAR POUSÉE — SCHUBSTART — ARRANQUE POR EMPUJE — AVVIAMENTO A SPINTA									
41SC25PSQ4-EU	1.1 - 4.5	—	—	2500	1.30	264	20	1/4	565
41SC10PSQ4-EU	1.1 - 4.5	1.7 - 9.0	—	1000	1.40	277	20	1/4	565

Series / Baureihe			
41	78 dBa	1/4" NPT	8 mm

(1) The torque range indicated in bold letter corresponds to the spring installed on the tool.
 (1) La gamme de couple indiquée en gras correspond au ressort monté sur la machine.
 (1) Kupplungsfedern werden mitgeliefert, fett gedruckte Drehmomentangaben gelten für werksseitig eingebaute Feder.
 (1) La gama de par en negrita corresponde con el muelle instalado en la herramienta.
 (1) La molla indicata in grossetto corrisponde a quella montata sulla macchina.